

ESP ASM, Standard and Indicating, Suffix Code

ASM Base No. 41046-XXX (STD); 41046-XXX3 (HFR) 44504-XXX (IND STD); 44504-XXX3 (IND HFR)	Suffix			
	1st Digit	2nd Digit	3rd Digit	4th Digit
Seal Material Buna-N (53010-XXX or 55343-XXX) Viton (53279-XXX or 55345-XXX) Neoprene (53013-XXX) EPDM (55680-XXX)	1 2 3 4			
Spring Light–Steel (Orange) (41047) Heavy–Steel (Blue) (41048) Light–Inconel (Yellow) (41049) Heavy–Inconel (Green) (41050) Ultra–Light-Steel (White) (46301)		1 2 3 4 5		
Sensing Unit 1 1/8-in. Piston, SS (44028-X010) 1/2-in. Piston, SS (44028-X020) 1/4-in. Piston, SS (44028-X030) 1/4-in. Piston, SS (44028-X090); 9/16 High Pressure Connection 3/16-in. Piston, SS, 20,000 psi (44028-1040) 2-in. Diaphragm, Aluminum (44028-X050) 2-in. Diaphragm, Stainless Steel (44028-X060) 4-in. Diaphragm, Aluminum (44028-X070) 4-in. Diaphragm, Stainless Steel (44028-X080)			1 2 3 4 5 6 7 8 9	

ASM Base No. 41046-XXX (STD); 41046-XXX3 (HFR) 44504-XXX (IND STD); 44504-XXX3 (IND HFR)	Suffix			
	1st Digit	2nd Digit	3rd Digit	4th Digit
Body				
Standard (44027-XXX)				–
Standard (Indicating) (44027-XXX5)				–
Hi Flo Rate (44027-XXX3)				3
Hi Flo Rate (Indicating) (44027-XXX4)				3

Part Number Examples

Part No. 41046

Part Number–41046-122

Complete assembly for 1,500 psi set point; Service–Standard; Spring–Heavy; Sensing Unit–1/2-in. Piston; Body–Standard

Part Number 41046-2333

Complete assembly for 3,000 psi set point; Service–H₂S; Spring–Light (Inconel); Sensing Unit–1/4-in. Piston; Body–High Flow Rate Full Stainless Steel

Part No. 44504

Part Number–44504-122

Complete assembly for 1,500 psi set point; Service–Standard; Spring–Heavy; Sensing Unit–1/2-in. Piston; Body–Standard

Part Number–44504-2333

Complete assembly for 3,000 psi set point; Service–H₂S; Spring–Light (Inconel); Sensing Unit–1/4-in. Piston; Body–High Flow Rate